

DA Series

Single and Multi-Tenant
Entry Security System



For Residential and Commercial Applications

Features & Benefits

- **Access control**
Provide entry security for up to four tenants sharing a common entrance
- **Visitor screening**
Safely and conveniently speak with visitors to determine their intent before unlocking the door
- **Replaces doorbell, easy to install**
Reduce installation costs by using existing doorbell wire. No doorbell? *No problem!* The system only requires two wires, making installation a snap!
- **Door release powered by system**
Have the convenience of door release without needing to purchase additional power
- **Simple to use**
Answer calls and unlock the entrance with simple, intuitive operation
- **Reliable and designed to last**
Have trouble-free use for years to come, even after the warranty expires!



Components

Entrance Stations - Select 1



DA-1DS
1-Call Audio
Entrance
Station



DA-2DS
2-Call Audio
Entrance
Station



DA-4DS
4-Call Audio
Entrance
Station

- Vandal resistant construction
 - Direct select button(s)
 - Backlit directory
 - Connects to door strike
 - Hands-free communication
 - Surface mount
- 6-7/8" H 3-15/16" W 7/8" D

Master Station & Power Supply



DA-1MD
Audio Tenant
Station

- Handset for privacy
- 7-7/8" H
3-1/2" W
2-1/2" D



PT-1211C
15V AC
Transformer


3-1/16" H
2-3/8" W
1-7/8" D

Box Set - Includes:

- 1 DA-1DS (Door Station)
- 1 DA-1MD (Master Station)
- 1 PT-1211C (Power Supply)



DA-1AS
Single
Tenant
Box Set




Accessories



EL-12S
Electric
Door Strike

4-1/8" H
1" W
1-1/4" D



DAR-1
Call Extension
Sounder

4-3/4" H
3-7/16" W
1-1/8" D

Specifications

Power Source	15V AC - use PT-1211C	Door Release	9.5-20V AC, 20Ω or higher resistance - use EL-12S
Communication	Handset (full-duplex)	Calling	Electronic tone with adjustable volume or mute
Wire Type	Door to Tenant: 2-cond., overall shield - use Aiphone #822202 or 2-cond., low cap, PE insulation, solid, non-shielded - use Aiphone #871802 Power to Tenant: 2-cond., low cap, PE insulation, solid, non-shielded - use Aiphone #871802		
Wire Distance	Door Station / Door Strike to Tenant Station / Power Supply (cumulative): 360'(22AWG) 1,020'(18AWG) Power Supply to Tenant Station: 180'(22AWG) 510'(18AWG)		

DA Series
Brochure
10/2013



ISO-14001 Certified



Aiphone Co. Ltd.

ISO 9001:2008 Certified



Aiphone Corp.

Deming Prize



Aiphone Co. Ltd.