

TD-HL


TD-H Selective Call Intercom with LED and Tone-Off Switch

DESCRIPTION:

The TD-HL series handset intercoms are designed for applications where visual indication of an incoming call is required. The red LED mounted on the top front of the unit lights whenever a station receives a call. The TONE OFF switch at the bottom allows the user to turn the standard call tone on or off at any time. The LED will light regardless of the switch position. Ideal for applications where silent signaling is required, such as radio stations or sound booths.

TD-HL FEATURES:

- Available in 1, 3, 6, and 12-call sizes (TD-1HL, TD-3HL, TD-6HL, TD-12HL)
- Selective calling with visual indication
 - Red LED lights to indicate an incoming call
- TONE OFF switch mutes call tone
 - Tone can be in the ON or OFF position
- Intermix various sized units to meet communication needs
- Door stations (max. 2) and paging zones can be added to the system

TD-3HL**Some Applications:**

- Radio Stations
- Sound Booths
- Churches
- Courtrooms
- Judicial Offices

SPECIFICATIONS:

Power Source:	12V DC, supplied by PS-12C
Power Consumption:	70mA max. per station
Wiring:	2 common plus 1 individual wire per station. (3 common with door station) TD-1HL: 4 cond.; TD-3HL: 7 cond.; TD-6HL: 10 cond.; TD-12HL: 16 cond.
Wiring Distance:	2000' with 22AWG
Mounting:	Surface mount to 1-gang box or ring. Desk mount with TDW- <i>n</i> Desktop Terminal Box
Dimensions (H x W x D):	8-1/4" x 4" x 2-7/8"

TD-HL Selective Call Intercom with LED and Tone-Off Switch

SPECIAL ORDER PRODUCTS:

TD-1HL	1-call handset w/ LED & Tone-Off switch
TD-3HL	3-call handset w/ LED & Tone-Off switch
TD-6HL	6-call handset w/ LED & Tone-Off switch
TD-12HL	12-call handset w/ LED & Tone-Off switch


STANDARD PRODUCTS:

TD-1H/B	1-call handset intercom
TD-3H/B	3-call handset intercom
TD-6H/B	6-call handset intercom
TD-12H/B	12-call handset intercom
TD-24H/B	12-call handset intercom

Accessories:

PS-12C	12V DC Power Supply, 1A
TDW-1	Desktop terminal box for TD-1H(L)
TDW-3	Desktop terminal box for TD-3H(L)
TDW-6	Desktop terminal box for TD-6H(L)
TDW-12	Desktop terminal box for TD-12H(L)
TDW-24	Desktop terminal box for TD-24H(L)
Others	See GLC or standard TD-H information

SYSTEM LAYOUT EXAMPLE:



ARCHITECTS/ENGINEERS' SPECIFICATIONS:

The system shall provide visual indication of an incoming call, and communication with the calling station via handset. The unit shall have a red LED mounted on the upper portion of the base, which shall illuminate when receiving a call. The unit shall be equipped with a TONE OFF switch, located on the bottom of the base. When the switch is in the OFF position, the tone shall be muted.

The LED shall illuminate when the tone switch is in either position. When the switch is in the ON position, the standard call tone shall be heard.

Units shall be available in 1, 3, 6, and 12-call sizes, and shall wall mount to a standard 1-gang box or ring. Optional desktop terminal box shall be available for desk mounting. Units shall be manufactured by Aiphone.