

IX SERIES

IP Addressable Edge Devices



EXPAND SECURITY AND COMMUNICATION ALONG YOUR NETWORK

IX SERIES

IP Addressable Edge Devices

Mix n' Match unlimited



Master Station



IX-MV

Video Master Station

- PoE
- 500 station address book capacity
- Hands-free communication with handset for privacy
- Wall or desk mount

The IX Series has infinite potential.

All IX Series stations connect directly to one another over a network. Verify guests, unlock doors, or assess emergency situations. Start with an IX-MV master station and network an infinite number of IX Series stations. Adding more master stations exponentially increases system capacity as each master station can connect to its own 500 stations.

IX Series Features

- Priority call queueing
- Transfer door calls to any master station
- All-in-one communication system to control video entry and access control
- View third party IP cameras on IX-MV master stations
- 24/7 streaming from video door stations
- ONVIF compliant video output
- Forward missed calls automatically



Video Stations



IX-DA

- Video Door Station
- PoE
 - Fixed camera
 - Plastic cover
 - Surface mount
 - Relay output



IX-DF

- Video Door Station
- PoE
 - Fixed camera
 - Stainless steel
 - Flush mount
 - Mounting box included
 - Relay output



IX-DF-HID

- Card Access Video Door Station
- PoE
 - Fixed camera
 - Stainless steel
 - Flush mount
 - Mounting box included
 - HID® ProxPoint® Plus Proximity Card Reader
 - Relay output



IX-DF-HID-I

- Card Access Video Door Station
- PoE
 - Fixed camera
 - Stainless steel
 - Flush mount
 - Mounting box included
 - HID® iCLASS® Smart Card Reader
 - Relay output

Audio Stations



IX-BA

- Audio Door Station
- PoE
 - Plastic cover
 - Surface mount
 - Relay output



IX-SS

- Audio Door Station
- PoE
 - Stainless steel
 - Flush mount
 - Mounting box included
 - Relay output

ADA Compliant Rescue Assistance Stations

- PoE
- Fixed camera
- Lettering and Braille signage
- LED call status indicator
- 2 Form-C relay outputs
- Stainless steel
- Flush mount
- Mounting box included



IX-DF-2RA

- Video Rescue Assistance Station
- Dual call buttons



IX-SS-2RA

- Audio Only Rescue Assistance Station
- Dual call buttons



IX-SS-RA

- Audio Only Rescue Assistance Station
- Single call button



IX Series Specifications

Power Source	Power Over Ethernet (802.3af)
Network Interface	10 BASE-T / 100 BASE-TX Ethernet (RJ-45)
Network Protocols	IPv4, IPv6, TCP, UDP, SIP, HTTP, HTTPS, RTSP, RTP, RTCP, IGMP, MLD, SMTP, DHCP, NTP, DNS
Bandwidth Usage	320Kbps to 8Mbps
Communication	Hands-free (VOX), push-to-talk (simplex), or handset (full-duplex)
Video Display	3-1/2" color LCD

Camera	Type: 1/4" color CCD, viewing area: 2' 1" vert. x 3' 1" horiz. at 20"
Video Stream	ONVIF Profile S
Door Release	Programmable Form C dry contact 24V AC/DC, 500mA
Wire Type	CAT-5e or CAT-6
Distance	Door Station to Network Node: 330'
	Master Station to Network Node: 330'

IX Series
Sales Sheet

To schedule a live product demonstration, visit www.aiphone.com/demo

